

## 204 INDICATOR



## **Model 204 Digital Weight Indicator**



Whether you require a permanent installation or a portable scale on the move, the 204 can be powered three ways:

- AC Power
- Alkaline batteries
- Rechargeable Ni-Cad batteries





Format and print custom tickets with nControl software, designed exclusively by Cardinal, allowing complete setup of the 200 series indicators from a PC.



## A VERSATILE, ECONOMICAL CHOICE!

Display: \_\_\_\_\_\_\_1" (25mm) high, 6-digit, 7-segment LCD

Protection Rating: .......................NEMA 12/IP55 stainless steel

**Units Conversion:** Pounds, kilograms, grams, and ounces **Load Cells:** Up to 4, 350 ohm minimum resistance

alkaline or rechargeable Ni-Cad batteries

Selectable Parameters: .........Decimal point, filtering, weight, sample rate, baud rate

Standard I/O:....(1) bi-directional RS232

Zero Tracking: 1 to 9d selectable
Zero Limit: 4% maximum range
Conversion Rate: 10 per second, max
Sensitivity: 1.2µV per division









Cardinal Scale reserves the right to improve, enhance, or modify features and specifications without prior notice.

Cardinal Scale Manufacturing Co. 203 E. Daugherty, Webb City, MO 64870 USA

Ph: 417-673-4631 or 800-441-4237 • Fax: 417-673-5001

www.CardinalScale.com